

Fig. 1A (Prior Art)

Example message generated by User A1's local mail program

140 { Date: Mon, 27 Nov 00 10:18:52 ~ 141  
From: "Alan Smith" <a1@abc.com> ~ 142  
To: x1@xyz.com, a2 ~ 143  
Subject: Test Message ~ 144  
150 { This message is a test. The end.

**Figure 1B (Prior Art)**

Example message as modified by local computing device 100 Sendmail program

From a1@abc.com Mon Nov 27 10:19:23 2000 ~ 145  
Message-Id: <9631121611.AA02124@abc.com> ~ 146  
Date: Mon, 27 Nov 00 10:18:52  
From: "Alan Smith" <a1@abc.com>  
To: x1@xyz.com, a2  
Subject: Test Message

This message is a test. The end.

**Figure 1C (Prior Art)**

Example message as modified by remote computing device 130 Sendmail program

147 ~ { From a1@abc.com Mon Nov 27 10:19:23 2000  
Received: from abc.com [216.122.95.01] by xyz.com (8.8.4/8.8.4) with ESMTP id BF02C24;  
Mon, 27 Nov 2000 10:21:46  
Message-Id: <9631121611.AA02124@abc.com>  
Date: Mon, 27 Nov 00 10:18:52  
From: "Alan Smith" <a1@abc.com>  
To: x1@xyz.com, a2  
Subject: Test Message

This message is a test. The end.

**Figure 1D (Prior Art)**

Example SMTP exchange as computing device 100 Sendmail connects to computing device 130 Sendmail

220-xyz.com Sendmail 8.6.12/8.5 ready at Mon, 27 Nov 2000  
10:22:23 -0800  
220 ESMTP spoken here  
220 ~ >>> EHLO abc.com  
250-xyz.com Hello abc.com, pleased to meet you  
250-EXPN  
250-SIZE  
250 HELP  
>>> MAIL From:<a1@abc.com>  
250 <a1@abc.com>... Sender ok  
>>> RCPT To:<x1@xyz.com>  
250 <x1@xyz.com>... Recipient ok  
>>> DATA  
354 Enter mail, end with "." on a line by itself  
{The message illustrated in Figure 1C is transmitted}  
>>> .  
250 GAA20115 Message accepted for delivery  
x1@xyz.com... Sent (GAA20115 Message accepted for delivery)  
Closing connection to xyz.com  
>>> QUIT  
221 xyz.com closing connection

**Figure 1E (Prior Art)**

Example SMTP exchange as virtual computing device 200 Sendmail connects to computing device 130 Sendmail

220-xyz.com Sendmail 8.6.12/8.5 ready at Mon, 27 Nov 2000  
10:22:23 -0800  
220 ESMTP spoken here  
220 ~ >>> EHLO bcd.com  
250-xyz.com Hello bcd.com (abc.com), pleased to meet you  
250-EXPN  
250-SIZE  
250 HELP  
>>> MAIL From:<b1@bcd.com>  
250 <b1@bcd.com>... Sender ok  
>>> RCPT To:<x1@xyz.com>  
250 <x1@xyz.com>... Recipient ok  
>>> DATA  
354 Enter mail, end with "." on a line by itself  
{The message illustrated in Figure 2C is transmitted}  
>>> .  
250 GAA20115 Message accepted for delivery  
x1@xyz.com... Sent (GAA20115 Message accepted for delivery)  
Closing connection to xyz.com  
>>> QUIT  
221 xyz.com closing connection

Error file

Host abc.com claimed to be bcd.com

**Figure 2E**




Fig. 2A

Example message generated by User B1's local mail program

Date: Mon, 27 Nov 00 10:18:52  
From: "Bob Smith" <b1@bcd.com> ~ 242  
To: x1@xyz.com, b2  
Subject: Test Message 2

This message is a test. The end.

**Figure 2B**

Example message as modified by virtual computing device 200 Sendmail program

From b1@bcd.com Mon Nov 27 10:19:23 2000 ~ 245  
Message-Id: <3431121623.4B0213D@bcd.com> ~ 246  
Date: Mon, 27 Nov 00 10:18:52  
From: "Bob Smith" <b1@bcd.com>  
To: x1@xyz.com, b2  
Subject: Test Message 2

This message is a test. The end.

**Figure 2C**

Example message as modified by remote computing device 130 Sendmail program

247 ~ From b1@bcd.com Mon Nov 27 10:19:23 2000  
Received: from abc.com [216.122.95.01] by xyz.com (8.8.4/8.8.4) with ESMTP id CD0A224;  
Mon, 27 Nov 2000 10:21:46  
Message-Id: <3431121623.4B0213D@bcd.com>  
Date: Mon, 27 Nov 00 10:18:52  
From: "Bob Smith" <b1@bcd.com>  
To: x1@xyz.com, b2  
Subject: Test Message 2

This message is a test. The end.

**Figure 2D**

Example message as modified by remote computing device 130 Sendmail program  
when sent by Virtual Domain Sendmail program on computing device 100

From b1@bcd.com Mon Nov 27 10:19:23 2000  
347 ✓ Received: from bcd.com [216.122.95.70] by xyz.com (8.8.4/8.8.4) with ESMTP id CD0A224;  
Mon, 27 Nov 2000 10:21:46  
Message-Id: <3431121623.4B0213D@bcd.com>  
Date: Mon, 27 Nov 00 10:18:52  
From: "Bob Smith" <b1@bcd.com>  
To: x1@xyz.com., b2  
Subject: Test Message 2

This message is a test. The end.

**Figure 3A**

Example SMTP exchange as Virtual Domain Sendmail program on computing device 100  
connects to computing device 130

220-xyz.com Sendmail 8.6.12/8.5 ready at Mon, 27 Nov 2000 10:22:23 -0800

220 ESMTP spoken here

361 ✓ >>> EHLO bcd.com

362 ✓ 250-xyz.com Hello bcd.com, pleased to meet you

250-EXPN

250-SIZE

250 HELP

>>> MAIL From:<b1@bcd.com>

250 <b1@bcd.com>... Sender ok

>>> RCPT To:<x1@xyz.com>

250 <x1@xyz.com>... Recipient ok

>>> DATA

354 Enter mail, end with "." on a line by itself

{The message illustrated in Figure 2C is transmitted}

>>> .

250 GAA20115 Message accepted for delivery


x1@xyz.com... Sent (GAA20115 Message accepted for delivery)

Closing connection to xyz.com

>>> QUIT

221 xyz.com closing connection

**Figure 3B**



**Figure 4**

Fig. 5

Create/Store Message  
For Virtual User  
Routine 500

Receive indication  
to create message 505

Receive indication of  
message text, of recipients,  
and optionally of subject 510

Determine virtual user  
name, virtual domain  
name, and current time 515

Add headers to message  
based on the determined  
information 520

Add message to outgoing  
message queue for the  
virtual machine supporting  
the virtual domain name 525

530  
More  
messages?  
Yes  
No

END 535

500  
505  
510  
515  
520  
525  
530  
535



Send Messages  
For Virtual User  
Routine

600 Fig. 6

